



GCC JC-240E PRINTER/CUTTER

GCC JC-240E Printer/Cutter allows users to apply on a wide variety of applications, such as wall Stickers, Vehicle Decoration, Sign, POS, POP, Label, Heat Transfer films... etc. Also, GCC JC-240E Printer/Cutter comes with the FlexiPRINT DX - GCC Edition RIP software which can easily complete the print and cut workflow with the user-friendly interface.

Features:

- ◆ Printer / Cutter in one machine
- ◆ Media Thickness up to 10mm
- ◆ Print resolution of up to 1440 DPI with 6 colors available
- ◆ Maximum Throughput 3.85 m²/hr(41.3 ft²/hr)
- ◆ Auto Media Calibration (AMC™)
- ◆ Enhanced AAS II Contour Cutting System
- ◆ Professional cutting functions
- ◆ Bundled FlexiPRINT DX - GCC Edition RIP software

■ Heat Transfer



■ Wall Stickers



■ Vehicle Decoration



■ Sign / POS / POP



■ Label





FlexiPRINT- GCC Edition software, which is designed to raise your productivity with the ease-to-use interface, offers the simple Print & Cut workflow.

Benefits:

- Smart, Easy and Powerful
- One comprehensive solution, from design to production
- Contour Cutting performed quickly and easily
- Superior colors
- Boosts output with high-productivity features
- Complete Color Separation Tools

Model	JC -240E	
Media printing width	Roll	590mm (23.2 inch)
	Single sheet	600mm (23.6 inch)
Max. media width	Roll	610mm (24.0 inch)
	Single sheet	625mm (24.6 inch)
Print head adjustment	AMC™	
Color Channel	8	
Color - Standard	CMYK	
Color - Option	Lc Lm	
Media thickness	10mm (0.394 inch) *1	
Roll weight	30kg (66.86 lbs)	
Roll core diameter	Inside: 76.2 mm (3 inch)	
Roll outer diameter	210mm (8.27 inch)	
Ink type	Eco -solvent	
Capacity	440 ml	
Ink Package	Cartridge	
Resolution	720 dpi (1440 dpi with Lc Lm - optional)	
Automatic-Aligning System	Completely Automatic Contour Cutting System for print to cut solution	
Max. Cutting Force	600 gram	
Max. Cutting Speed	720 mm /sec (28.3 ips)	
Distance Accuracy -When printing	Less than $\pm 0.3\%$ of distance traveled, or $\pm 0.3\text{mm}$ (0.0118 inch), whichever is greater	
Distance Accuracy -When cutting	Less than $\pm 0.4\%$ of distance traveled, or $\pm 0.3\text{mm}$ (0.01 inch), whichever is greater	
Repeatability - When cutting	$\pm 0.1\text{mm}$ (0.0039 inch) or less	
Alignment accuracy for printing and cutting	$\pm 0.5\text{mm}$ (0.0197 inch) or less	
Alignment accuracy for printing and cutting when reloading media	Less than $\pm 0.5\%$ of distance traveled, or $\pm 0.3\text{mm}$ (0.01 inch), whichever is greater	
Connectivity	Ethernet (10BASE -T/100BASE TX Automatic switch)	
Voltage requirement	115/250VAC 50/60HZ	
Power consumption -Operating	115V AC (60HZ) (Max. 384W)	
	220V AC (50HZ) (Max. 324W)	
Power consumption -Stand by	115V AC (60HZ) (Max. 72W)	
	220V AC (50HZ) (Max. 72W)	
Acoustic noise level -During operation	64dB (A) or less	
Acoustic noise level -During stand by	41dB (A) or less	
Environment (Temperature/Humidity)	22°C ~ 30°C (71.6°F ~ 86°F) / (40% ~ 60% humidity)	
Dimension	1,618 (W) x 870 (D) x 1,301 (H) mm	
	63.7 (W) x 34.2 (D) x 51.2 (H) inch	
Weight	107 kg	

*1: Only available with the add-on flat table optional item.

*2: Above specifications are subject to change without prior notice.



www.GCCworld.com



GCC Headquarters	4F, No.236, Fude 2nd Rd., Xizhi Dist., New Taipei City 22151, Taiwan	886-2-6616-6692	Fax : 886-2-2694-6875
GCC China	No.1, Chen Feng Road, Yushan, Kunshan, Jiangsu 215300, China	86-512-5726-1515	Fax : 86-512-5726-1518
GCC Europe B.V.	Eglantierbaan 43-45, 2908 LV, Capelle a/d IJssel, The Netherlands	31-10-458-9367	Fax : 31-10-451-9874
GCC America, Inc	323 Paseo Tesoro, Walnut, CA 91789, USA	1-909-718-0248	Fax : 1-909-718-0251
		US & Canada Only	Toll Free: 1-888-284-5211